

Mouldboard Ridger With Wheel

ARAS- T



 **ARMADA**

ARAS-T, Mouldboard Ridger with Wheel

The primary soil tillage machine is mounted from tractor's hydraulic lifting unit and universal three point linkage system. Therefore transportation to the field can be easily done. Furrow opener is placed over adjustable profile chassis and also it is manufactured as with or without wheel. It has an opportunity to enter between rows as demanded width due to its adjustable moldboards. The usage aim of the machine is to open furrows between rows and ridging for row-planted seeds such as; corn, sunflower, cotton, etc.



Technical Specifications*	Unit	ARAS-T 2	ARAS-T 3	ARAS-T 4	ARAS-T 5	ARAS-T 6
Number of The Disc	pcs	2	3	4	5	6
Total Width (W)	mm	1300	2100	2900	3700	4400
Total Length (L)	mm	1000	1000	1000	1000	1000
Total Height)	mm	1750	1750	1750	1750	1750
Distance Between Furrows	mm	700-900	700-900	700-900	700-900	700-900
Bottom Width of The Canal	mm	250	250	250	250	250
Canal Depth	mm	200-350	200-350	200-350	200-350	200-350
Canal Width	mm	300-340-360				
Dept Wheels		Optional				
Required Power	hp	45-50	50-60	65-75	80-90	95-1100
Weight	kg	300	450	520	620	700

* Armada reserves rights to change them without notice.





ARMADA

Agricultural Machinery