

Mouldboard Plough Ridger Fixed and Foldable ARAS



 **ARMADA**

ARAS, Mouldboard Ridger Fixed and Foldable

The primary soil tillage machine is mounted and trailed from tractor's hydraulic lifting unit and universal three point linkage system. Therefore transportation to the field can be easily done. Furrow opener is placed over adjustable angle chassis. It has an opportunity to enter between rows as demanded width due to its adjustable moldboards. The usage aim of the machine is to open furrows between rows and ridging for row-planted seeds such as; corn, sunflower, cotton, etc

Fixed Type



Foldable Type



Technical Specifications*	Unit	ARAS 2	ARAS 3	ARAS 4	ARAS 5
Number of The Bodies	pcs	2	3	4	5
Total Width (W)	mm	1300	2100	2900	3700
Total Length (L)	mm	700	800	800	800
Total Height (H)	mm	1250	1250	1250	1250
Distance Between Bodies (B)	mm	600-950	600-950	600-950	600-950
Furrow Bottom Depth	mm	250	250	250	250
Furrow Width	mm	300-340-360	300-340-360	300-340-360	300-340-360
Working Dept (max)	mm	200-350	200-350	200-350	200-350
Required Power	hp	35-40	40-45	60-70	80-90
Weight	kg	147	223	370	450

* Armada reserves rights to change them without notice.





ARMADA

Agricultural Machinery